

24" TFT Full HD 16:9 Capacitive Touch Monitor with 1x USB, 1x COM, 1x VGA, 1x DVI-D and 1x DisplayPort, 9V~48V

FEATURES

- 24" TFT Full HD 16:9 LCD with Projected Capacitive Touch
- Max. Resolution 1920x1080
- Designed with Aluminum Die-Cast Front Frame
- IP65 Compliant Front Panel
- 1x USB, 1x COM, 1x VGA, 1x DVI-D, 1x DisplayPort, 1x Audio
- Built-in Two 5W Internal Speakers
- Convertible Display System (CDS) Supported
- Supports Panel / VESA / Rack Mounting
- OPTION! (Resistive 5-wire Touch / Glass)
- 9~48VDC via 3-pin Terminal Block





SPECIFICATIONS

Operating Temp.	:	Ambient with air flow: -5°C to 60°C (With extended temperature peripherals; Ambient with air flow According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
Approval	:	EMC: CE, FCC Class A
Forsyning	:	Power Requirement: 9~48VDC Connector 3-pin Terminal Block Connector Power Adaptor Optional AC/DC 12V/5A, 60W Power Adapter
Kontrast	:	5000:1
LCD	:	24" 16:9
Lyd	:	AMP 5W + 5W (Internal Speaker)
Montering	:	vesa, panel, (oPTION raCK MOUNT NEED TO ORDER kit!)
OSD	:	LCD On/ LCD Off, Auto, Menu, Up and Down (Multi-language)
Synsfelt	:	178/178
Weight	:	kg. 7,76

