

L-CON modul med digitale udgange

FEATURES

Intelligent Controller with Webserver
 Logical functions such as: IF-THEN-ELSE
 No programming. Just pick, click and finished
 Supports: I/O module, counter, timer, email
 Modbus/TCP protocol to SCADA software seamless integration
 IEEE 802.3af compliant Power over Ethernet (PoE)
 1 x RJ45 - 10 / 100Mbit Ethernet
 8 x Power relay output, COM NO
 Relay switch: 30VDC, 250VAC 5A, only resistive load
 Supply voltage: PoE or 12 - 48VDC / 5.5Watt





SPECIFICATIONS

Operating Temp.	:	- 25°C - 75°C
Forsyning	:	12 - 48 VDC via klemrække eller via PoE
Isolation	:	Optisk 2500 VRMS til analoge og digitale ind- og udgange i forhold til strømforsyningen. Magnetisk 1500 V fra netværksinterface til strømforsyningen
Netværk	:	10/100 Mbit m/RJ45 hunstik
Protokol	:	Understøtter Modbus/TCP
Udgange	:	8 stk. relæudgange type A (slutte) AC: 250 V og 5 A DC: 30 V og 5 A Lukketid er 6 ms og åbnetid er 3 ms
Dimensioner	:	123 x 72 x 35 mm

