

1 channel temperature/humid logger 0 - +55°C, 10 - 95% RH. Wireless to collects up to 150m, BT. External sens. Battery operation

FEATURES

- Wireless Temperature and Humidity Logger with memory
- Bluetooth to T&D Thermo APP
- Sending measurement data to Data Collector (Base Station) at 870MHz
- Distance between Data Logger and Data collector up to 150 meters
- Battery operation up to 10 months at an upload per day
- 2 x 8,000 measurements in memory with the date and time stamp
- Accuracy of measurement: max. + / - 0.3 ° C, +/- 5% RH
- Removable external sensor. IP64 with O-ring
- Free Cloud service: TD WebStorage for Data Collector
- LCD display shows current measurements
- PC software: tools and presentation included
- Data Logger setup with Data Collector Optical
- Dimensions: 62 x 47 x 19 mm
- Battery type: LS14250 x 1





Svensk Binär Teknik

LOG-WL503

SPECIFICATIONS

| | | |
|-----------------|---|--|
| Operating Temp. | : | - 40 - 80 °C |
| Andet | : | Ekstern temperaturføler og fugtføler medfølger til LOG-WL503 |
| Data | : | 2 x 8.000 målinger |
| Måleområde | : | 0 - 55 °C fugt 10 - 95 % ekstern føler |



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.