



10.1" LCD Touch Screen Alu Front, Projected Capacitive Touch 1280x800 16:10, IP66 Front, DC 9 ~ 36V

FEATURES

- 10.1" TFT 1280x800 (16:10)
- Front panel IP66 Standard / IP69K Option
- Aluminum cabinet
- VGA, DVI, HDMI and DP Input
- Supply voltage: DC 9 ~ 36V
- Contrast : 800:1
- Brightness: 350 Nits Standard / 1000 Nits Option
- Touch Via USB: Projected Capacitive Standard / Resistive Option / No Touch Option
- Touch Via RS232: Option
- VESA 100 and Panel Mount
- Dimensions: 285 x 189 x 48.9mm
- Weight: 1.9 kg
- Operating temperature: 0 ~ +50°C Standard / -20 ~ +60°C Option





SPECIFICATIONS

Andet	:	15G peak acceleration (11 msec. duration) / Operation
Drivere	:	eGalaxTouch
Forsyning	:	DC 9 ~ 36V
Indgang	:	USB
IP-Tæthed	:	IP66 front
Kabinet	:	Aluminum die-casting chassis
Montering	:	Panel and VESA
Opløsning	:	1280x800 16:10
OS SUPPORT	:	Windows XP, Vista, 7, 8, CE, Mac og Linux
Touch	:	USB, PCAP
VESA standard	:	100 x 100mm
Weight	:	1.9 kg





Svensk Binär Teknik

MON10.1-TFT-T

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.