

MON5-S

Professional 5" service monitor for Analog camera setup. Built-in battery. With BNC, HDMI, VGA, 12VDC out

FEATURES

- Portable Service monitor
- AHD / TVI / CVI / CVBS coax in and out, HDMI in, VGA in. PAL / NTSC
- 12VDC 1A output for camera
- 800 x 480 (5: 3) 5 "TFT color screen.
- Supports Pan-Tilt-Zoom Pelco-D / P PTZ via RS485
- Supply: 5VDC via Micro USB-B connector.
- 5200 mAh battery, up to 11 hours battery life
- Suitable for camera installers
- Some IP cameras have CCTV output (BNC)
- Cannot be used for IP cameras without BNC



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

MON5-S

SPECIFICATIONS

Batteri	:	2 x 3.7V / 2600mAh 18650 battery
Forsyning	:	230 VAC netadapter 5VDC, 1A medfølger
Indgang	:	HDMI
Kabinet	:	Plastik
Maks. opløsning	:	1920 x 1440
Skærm	:	800 x 480 pixel
Skærm	:	5"
Dimensioner	:	174 x 114 x 36 mm

