

1200 Watt ATX power supply, P4, PCIE, SATA cables FEATURES

1200 W ATX med P4, PCI-Express og SATA
 VOLTAGE 90-264VAC
 FREQUENCY 47-63HZ
 INPUT CURRENT 15 (RMS) FOR 120 VAC / 8A (RMS)
 FOR 230 VAC
 INRUSH CURRENT 40A MAX. FOR 120 VAC / 80A
 MAX. FOR 230 VAC
 PFC CAN REACH THE TARGET OF 95% @230VAC,
 FULL LOAD
 HOLD UP TIME WHEN POWER SHUTDOWN DC
 OUTPUT 5V MUST BE MAINTAIN 12ms IN
 REGULATION LIMIT AT NORMAL INPUT
 VOLTAGE EFFICIENCY TYPICAL 80-85% AT 25°C 115V
 FULL LOAD
 POWER GOOD SIGNAL ON DELAY 100ms TO 500ms
 OFF DELAY 1ms
 OVER POWER PROTECTION TRIP POINT TOTAL
 POWER MIN. 110%, MAX. 150%
 OVER VOLTAGE PROTECTION +5V→5.8V→6.7V,
 3.3V→3.6V→4.3V, +12V→13.2V→15V
 OVER CURRENT PROTECTOIN: +3.3V→37.4~51A,
 +5V→37.4~51A, +12V→110~150A
 SHORT CIRCUIT +5V→-5V→+12V→-12V→+3.3V
 RESTART AFTER PROTECTION
 TEMPERATURE RANGE OPERATING 0°C→40°C
 LEAKAGE CURRENT: 1.5MA MAX. AT NOMINAL
 VOLTAGE VAC
 EMI NOISE FILTER : FCC CLASS B , CISPR22 CLASS B
 SAFETY : TO MEET UL, CUL, TUV, CCC
 REMOTE ON/OFF CONTROL
 160x150x86(mm)





Svensk Binär Teknik

PS1200ATX

SPECIFICATIONS

Effekt	:	1200W
Maks. effekt	:	1200W
Molex	:	7
Output	:	Max. +12VDC 100A, Max +3.3 VDC 34A, Max +5VDC 34A
Pin	:	24
SATA	:	6
Dimensioner	:	86 x 150 x 160 mm (H x B x D)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.