

PS300ATX1U

300 Watt ATX power supply 1 Unit industrial PCs FEATURES

Input voltage: 90-264Vac
Input frequency: 47-63Hz
Input current: 115Vac @ 6A, 230Vac @ 3A
80 Plus Bronze
Internal 4 cm fan with IEC 62368 standard vents opening
Short circuit protection on all outputs
Working temperature: 0°C to 50°C
Storage temperature: -20°C to + 80°C
Efficiency: 80 Plus Bronze Working humidity: 85% RH non-condensing
Storage humidity: 95% RH non-condensing
CE, FC, Tüv, E190414
Dimension (L x W x H): 190 x 100 x 40.5 (mm)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



PS300ATX1U

SPECIFICATIONS

Indgangsspænding	:	90-264Vac Input frequency: 47-63Hz Input current: 115Vac @ 6A, 230Vac @ 3A
Luftfugtighed	:	Working: 85% RH non-condensing Storage: 95% RH non-condensing
Maks. effekt	:	300 W
Udgangseffekt	:	+3.3v: 12A; +5v: 14A; +12V: 25A; -12V: 0.3A; +5Vsb: 3A. the +3.3V and +5V max total (80W). -5V on request
Operating Temperature	:	0°C to 50°C
Dimensioner	:	(L x W x H): 190 x 100 x 40.5 (mm) Environment 7.49 x 3.94 x 1.6 (inch)

