

SDI booster - SDI video repeater over coax cable up to 200m

FEATURES

- Transmit the SDI signal up to 200 meters
- Up to 1200 meters with 5 boosters in extension





SPECIFICATIONS

Operating Temp.	:	0° - 55° C, luftfugtighed 0 ~ 95 %
Afstand	:	SD-SDI (270/540Mbps) op til 400M (1000 meter v/ 5 REP-SDI) HD-SDI (1,45Gpbs) op til 200M (1000 meter v/ 5 REP-SDI) Dual HD-SDI (2,97Gpbs) op til 100M (500 meter v/ 5 REP-SDI)
Indgang	:	1 x 75Ω BNC stik, RS485 Tx+, Tx- (skrueterminal)
Indikatorer og kontakter	:	1 x Power LED (grøn)
Opløsning	:	HDTV input fra 480i til 1080p v/ 60Hz
Standarder	:	SD-SDI (SMPTE 259M/344M), HD-SDI (SMPTE 292M), dual link HD-SDI (SMPTE 372M), og dual speed HD-SDI(SMPTE 424M)
Strømforsyning	:	230VAC til 12VDC 1,5 A strømforsyning medfølger
Udgange	:	1 x 75Ω BNC stik, RS485 Tx+, Tx- (skrueterminal)
Dimensioner	:	27 x 67 x 91 mm

