

## RFID Reader for Mifare Ultralight and Mifare1 Standard Card, Wiegand, MSR ABA TK2 and RS232 Interface, 5 - 18VDC

### FEATURES

- Reading distance: Up to 5 cm
- Frequency: 13.56 MHz
- Read Mifare Ultralight and Mifare F1 Standard Tag
- Mifare 1024/4096 byte, Ultralight 512bit, ISO 14443A
- 3 in 1 interface : Wiegand, MSR ABA TK2 and RS232
- LED and Buzzer
- Quick Data Transfer
- Weatherproof, ABS
- Cable Length: 90 cm
- Cable is not terminated with DB9
- Easy to install
- Supply: 5 - 18VDC (Liniary PSU)
- Dim: 83 x 47 x 16 mm





## SPECIFICATIONS

|                 |   |                                                          |
|-----------------|---|----------------------------------------------------------|
| Operating Temp. | : | -10 til +60 °C                                           |
| Andet           | : | Monteret med 90 cm kabel                                 |
| Interface       | : | Wiegand og RS232                                         |
| Rækkevidde      | : | Op til 5 cm                                              |
| Tag-typer       | : | Mifare Classic 1k og 4k Mifare Ultralight Mifare DESFire |
| Udformning      | : | Til montering på væg                                     |
| Dimensioner     | : | 47 x 83 x 16 mm                                          |

