Svensk Binär Teknik

RFID-R10N85

RFID Reader 125kHz EM Standard Hex 40bit. 2-wire RS485 half-duplex. Command-controlled from PC. Up to 16 on RS485 bus. 12vdc.

FEATURES

- RS485 Command Controllet Ready / Read
- Set to Read. Called to Transfer Take UID Code
- 10 digit Hex - (26 digits for PC)
- 2-wire RS485 Half-duplex.
- 125 kHz EM format.
- 12vdc 0.2a (MDFollows not)
- Dimensions: 113.5 x 45.6 mm (L X B)

Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden
042 14 10 85
salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

Svensk Binär Teknik

RFID-R10N85

SPECIFICATIONS

Baudrate	:	9600
Formater	:	EM
Frekvens	:	125kHz
Interface	:	RS-485
Kabel	:	1 Meter
Strømforsyning	:	12VDC 0.2A (mdfølger ikke)
Dimensioner	:	113.5 x 45.6 mm (L x B)

Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden
042 14 10 85
salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.