

RFID 2.45GHz reads / write for active RFID tag. Range up to 140 m. Ethernet, RS232, RS485. Removable antenna

FEATURES

- Long Range 2.45GHz RFID reads and writes for 140 m Range
- Programmable parameter
- 1 x RJ45 (10/100 Mbit)
- 1 x RS232 (RX, TX)
- 1 x RS485 2-wire Protocol: ICMP, ARP, IP, TCP (Server / Client), UDP, DHCP, HTTP
- Supply voltage: 7 - 15 VDC / 4 Watt
- Dimensions: 107W x 138h x 30D (mm)
- Weight: 222g
- easy installation





SPECIFICATIONS

Operating Temp.	:	-20 til +65 °C
Antenne	:	Rundstrålende (omnidirektionel)
Forsyning	:	7-15 VDC 3,6W. 12 VDC, 1.5 A 230VAC adapter medfølger
Frekvens	:	2,40 - 2,48 GHz
Interface	:	RS232, RS485 og 10/100Mbit Ethernet interface
Læseafstand	:	Op til 140 m afhængig af tag
Protokol	:	ICMP, ARP, IP, TCP (Server/Client), UDP, DHCP, HTTP
Software	:	Administrationssoftware til indstilling af parametre, demosoftware til afprøvning af funktionerne og SDK til udvikling af egen software medfølger.
Dimensioner	:	107 x 138 x 30 mm. Vægt 222 g

