



Svensk Binär Teknik

RFID245TAG2K-V

RFID tag with hole for pendant, button for emergency, signal or on / off, ink. vibration sensor FEATURES

- Active RFID Tag with hole for pendant + vibration sensor
- 2.45 GHz read and write
- Transmission distance 90 m
- Dimensions: 42W x 30H x 10D (mm)
- weight: 9.1g
- wireless programming
- Digital RSSI/LQI Data
- low battery warning
- Supplied without 1 x 2032 battery
- Built-in button
- FCC, CE Certified



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

RFID245TAG2K-V

SPECIFICATIONS

Afstand	:	Transmission afstand op til 90 M
Chok/Vibration	:	Vibrations funktion er inkluderet
Mål og vægt	:	42 x 30 x 10 mm, 10g



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.