



Svensk Binär Teknik

RFID865TAG-B

UHF RFID Tag, 865MHz, R/W 96bit EPC / 512bit User, for metal base, 0 - 5 m, depending on antenna gain FEATURES

RFID TAG mounting on metal
Passive 865 MHz RFID PVC Tag (860 - 960MHz)
0 - 5 meters depending on antenna Gain
TAG Format 138 x 30 x 5 mm
protocol: ISO 18000-6C (R / W) - 96bit EPC / 512bit
User
TAG ID (UID) in the second sector on the roof.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

RFID865TAG-B

SPECIFICATIONS

Operating Temp.	:	-20°C÷+60°C
Frekvens	:	860-960MHz
Protokol	:	ISO 18000-6C÷EPC Clas 1 Gen 2
Weight	:	30g
Dimensioner	:	249mm×13.8mm×6mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.