



Svensk Binär Teknik

RFID865TAG-S

UHF RFID 865MHz TAG, (R/W) - 96bit EPC/512bit User,
Passive, Adhesive Paper, 0-10 M Depending on
Antenna Gain

FEATURES

Passive 865 MHz RFID PVC Tag
0 - 10 m depending on antenna Gain
ISO Short format 86 x 54 x 0.5mm
protocol: ISO 18000-6C (R / W) - 96bit EPC / 512bit
User
Tag ID UID in the second sector.
Read and write: 100,000 times
Material: Paper
Operating temperature: -20 - + 85 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

RFID865TAG-S

SPECIFICATIONS

Operating Temp.	:	-20°C ~ +85°C
Frekvens	:	860 to 960 MHz
Hukommelse	:	96bit EPC, 512bit User
Protokol	:	ISO 18000-6C EPC Clas 1 Gen 2
Dimensioner	:	85mm × 54mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.