

USB3HUB4DIN

4 port USB 3.0 HUB for DIN rail for 7 - 24VDC external power supply. DC from USB port can be disconnected
FEATURES

- 4 port USB 3.0 HUB with DIN rail mounting
- Can be powered from 7-24 VDC
- Provides good noise immunity
- Up to 900mA per port. by external supply.
- USB cable for PC included
- Voltage ONLY from terminal - int. jumper on DIS
- Voltage from USB and clamp - int. jumper on ENA





Svensk Binär Teknik

USB3HUB4DIN

SPECIFICATIONS

Operating Temp.	:	0 - 55° C
Forsyning	:	Spændingforsynes med 7-24 VDC via skrueterminal eller fra USB porten direkte. Strømforsyning medfølger ikke. Evt. brug DC24V625MA-D
OS SUPPORT	:	Understøttes af Windows 98, ME, 2000, XP, Vista, Windows 7 og 8
Stik	:	4 x type A hanstik og 1 x type B hunstik
Dimensioner	:	14,25 x 6,52 x 2,63 cm (H x B x D)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.