

## RS232 serial extender up to 250 meters via RJ45 point to point cable. 5VDC with Power over Cable

### FEATURES

- RS232 Rxtends up to 250 meters over RJ45 cable
- Baud rate: 110 ~ 921,600, 8-bit
- Use STP (shielded) patch cable - straight through
- The network cable must not be connected to the patch panel
- 1 x 5VDC/1A - the power supply supplies both devices (PoC)
- Important: If the distance is long, 2 power supplies are recommended
- Important: If the network cable is of poor quality, use 2 power supplies





Svensk Binär Teknik

BOOST-RS232RJ45+

## SPECIFICATIONS

|                |   |                                        |
|----------------|---|----------------------------------------|
| Baudrate       | : | 110 - 921.6k, 8 databit                |
| Standarder     | : | RS232 (5 ledere)                       |
| Stik           | : | DB9 han / DB9 hun / RJ45 hun / DC Jack |
| Strømforsyning | : | 5VDC/1A adapter                        |
| Dimensioner    | : | 50 (B) x 67 (D) x 23mm (H)             |



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.