

CNV232I232+

Seriell RS232 optisk isolator. Beskytter tilsluttet udstyr og computer

FEATURES

- Max. transfer rate 115 kb/s
- transferred signals full RS232 - Rx/D, Tx/D, RTS, CTS, DSR, DTR, DCD, RI
- optical indication Rx/D, Tx/D
- max. line length 15 m
- connector RS232 - PC side D - SUB 25 pin F
- connector RS232 - DEVICE D - SUB 25 pin M
- connector power supply 1,3mm plug
- optical separation - optocouplers 2,5 kV
- galvanic separation - DC/DC converter 1 kV
- overvoltage (soft) protection - supply 600W 10/1000us
- power supply +9 to 30V DC
- input supply max. 1,2 W
- dimension 91 x 22 x 54 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

CNV232I232+

SPECIFICATIONS

Isolation	:	1000 VAC, Tx, Rx, RTS, CTS, DSR, DCD og DTR
Strømforsyning	:	Ekstern strømforsyning på 9 VDC, 500 mA medfølger. Forsyning er fælles med den ene RS232 stelindgang; skærm er ført igennem.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.