

ESW6POE+

6 port switch 4 x 10/100Mbit + 2 x 10/100Mbit RJ45 uplink, POE+, Managed, 48VDC Jetnet 4706 FEATURES

REMAINDER SALE

- 4 x 10/100Mbit RJ45 Managed switch with PoE+
- 2 x 10/100Mbit RJ45 redundant uplink ports
- DC 48V Power Input (power supply not included)
- Up to 25 Watts per port
- Max. 80 Watt total power
- Multiple Super Ring technology (MSRTM), 5ms recovery time
- Dual Homing (RDHTM)
- IGMP snooping multicast
- Built-in hardware watchdog timer for system auto-reset
- 40~60°C operating temperature



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Operating Temp.	:	-10° til +60° C
LED	:	Indikation af on/off, link og aktivitet
Porte	:	6 x 10/100 Mbit porte med RJ45-stik og automatisk detektering af lige/krydset kabel
Strømforsyning	:	Redundante indgange til strømforsyning; 2 x terminalblok til 48 VDC. Switchen bruger 11,5 watt maksimalt. Det samlede strømforbrug er afhængig af PoE belastningen
Tilbehør	:	Leveres med DIN skinnebeslag, vægbeslag, manual på CD og quickguide
Understøtter	:	Understøtter QoS (Quality of Service), hvor bestemte typer netværkstrafik kan prioriteres højere end andre typer (f.eks. ved maskinstyring eller IP-telefoni). Desuden understøttes VLAN
Watchdog	:	overvåger driften og laver automatisk reset hvis enheden "fryser"
Dimensioner	:	136 mm (H)

