

1 PORT SERIAL PORT SERVER RS232 / 422/485 with 3 x digital input, 3 x relay. 1 x RJ45. 9 - 24VDC. FEATURES

- External COM port and DI / DO via Ethernet and Internet
- built-in web server
- 3 x Shift relays Expanses Max. 30 VDC 1A
- 3 x digital contact inputs
- 1 x RS232 (DB9 Male), RS422 or RS485 (screw terminal)
- 1 x Ethernet 10 / 100Mbit
- Power supply from 9 to 24 VDC





SPECIFICATIONS

CPU	:	16 bit CPU, 100 MHz
Operating Temp.	:	0 - 55 °C
Hukommelse	:	2MB RAM, 256 KB ROM
Indgang	:	3 indgange der aktiveres ved at de ligges til stel
Kabinet	:	Stålkabinet i format 22 x 67 x 93 mm (H x B x D)
Netværk	:	1 x 10/100 Mbit Ethernet
Porte	:	En port, der kan bruges som RS232 eller RS422/485, 1200 bps - 230,4 Kbps
Protokol	:	TCP, UDP, DHCP, HTTP, ICMP, ARP, ICMP, Telnet, SMTP
Signaler	:	RS232: Rx , Tx , RTS , CTS , DTR , DSR og DCD. RS422: Rx+/- , Tx+/- , (4 - leder fuld duplex). RS485: Data + og Data - (2-leder halv duplex)
Skærm	:	9 lysdioder viser Tx, Rx, netværks- og systemstatus samt status på de digitale indgange og relæ udgangene
Stik	:	DB9M til RS232 og skrueterminaler til RS422/485. 1 x RJ45 til Ethernet. Spændingsforsyning: 1 x 5,5 mm DC jackstik (hun) til medfølgende 220 VAC adapter eller via skrueterminal. Skrueterminaler til relæudgange og isolerede digitale indgange
Strømforsyning	:	Kræver 9 - 24 VDC maks. 500 mA (ustabiliseret), netadapter medfølger





Svensk Binär Teknik

ETH1SER-R3I3+

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.