

8 x RS232 serielle porte til PCI, XP / Vista / 7 / 8.x /  
10 (X86/X64) / 11,

## FEATURES

Expands 8 independent RS-232 serial port with communication speeds up to 115.2Kbps.  
High reliability SUN1999 16C950 compatible UART controller on-board.  
Compliance with PCI 33MHz Ver. 3.0/2.3/2.2/2.1 specification.  
Supports both 64-bit & 32-bit PCI bus slot and 3.3V & 5V power.  
On-chip hardware auto flow control to guarantee no data loss.  
Built-in  $\pm 2$ KV ESD protection for all serial signals.  
Plug-n-Play, I/O address and IRQ assigned by BIOS.  
Certified by CE, FCC, RoHS, and Microsoft WHQL approval.  
Support Microsoft Windows, Linux, and DOS.  
Windows ClientXP / Vista / 7 / 8.x / 10 (X86/X64) / 11  
Windows Server2003 / 2008 / 2012 / 2016 / 2019 / 2022 (X64)  
**Windows Embedded**XP Embedded / POSReady 2009 / POSReady / Embedded System 2009  
**Linux**Linux 2.x / 3.x / 4.x / 5.x / 6.x  
DOSDOS\***UNIX**FreeBSD / QNX / SCO OpenServer / SCO UnixWare / Solaris\***IBM OS/2**WARP 3/WARP 4





## SPECIFICATIONS

|          |   |                                                    |
|----------|---|----------------------------------------------------|
| Andet    | : | Maks. 1 kort i hver pc                             |
| Baudrate | : | Maks. 921,6 Kbit/s                                 |
| Drivere  | : | Windows 2000, XP, Win7, Win8, 2003, Vista og Linux |
| FIFO     | : | 32 bytes                                           |
| PCI      | : | 3,3 og 5 V. Kompatibel med PCI-X                   |
| Porte    | : | 8 x RS232                                          |
| Stik     | : | 8 x DB9 han (via blækspruttekabel der medfølger)   |
| UART     | : | 16C650                                             |

