



Svensk Binär Teknik

CNV-USB-CAN-I

USB to CAN buss converter, isolated FEATURES

Connect CAN Bus equipment over USB ports
supports CAN 2.0A and CAN 2.0B protocols
with 2.5kv isolation from Can to USB port
supplied via USB. Max. 250MA @ 5V DC
OS Support: Windows 2000 Up to Windows 10,
Linux Kernel 2.6+, Mac OS X



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

CNV-USB-CAN-I

SPECIFICATIONS

Operating Temp.	:	0°C to 60°C
Hastighed	:	Op til 1 Mbit på CAN bussen
Interface	:	USB 2.0 - bagudkompatibel til USB 1.1
OS SUPPORT	:	Windows 2000, XP, 2003, Vista, Win7/8/10
Stik	:	DB 9 han stik til CAN bus. USB type B hun stik



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.