

Electronic door magnet 12 / 24VDC switching 0.5A / 0,25A. Holding force of up to 272kg

FEATURES

Electronic door magnet with a holding force of up to 272kg

Options: Open-alarm, shut down timer 2-70 sec.

Option: alarm relay output

Aluminum with epoxy by the coil

12VDC or 24VDC is selected with jumper. 0,5A / 0,25A

Magnetic: 250 x 42 x 26 mm

Door plate: 185 x 38 x 12 mm

Mounting plate: 250 x 25 x 5 mm

Anti-magnetic feature

Operating temperature: -10 ~ 55C





Svensk Binär Teknik

DOOR-MAGNET+E

SPECIFICATIONS

Operating Temp.	:	-10~55°C
Forsyning	:	Valgfri mellem 12 VDC (500 mA) eller 24 VDC (250 mA). Medfølger ikke. Brug f.eks. DC12V/1A-R-Q
Weight	:	2 kg
Dimensioner	:	Magnet:(L) 250, (W) 42, (D) 26 mm Armature plate:(L) 185, (W) 38, (D) 12 mm Mounting plate:(L) 250, (W) 25, (D) 5 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.