



UPS2000LCD

2 kVA / 1.2kW UPS uninterruptible power supply with LCD indicator. Incl. 2 x 12V / 9aH battery, 3 x 3 x IEC Schuko

FEATURES

- 2000 VA UPS for industrial use
- 3 x Schuko
- 3 x IEC
- Modified sine wave
- 6 hours recharge time
- Alarm v. Low battery and overvoltage mm
- 1 x USB (type B)
- Operating temperature: 0-40 °
- Supports automatic shutdown via software included. 2 x 9 Ah battery





SPECIFICATIONS

Operating Temp.	:	0-40°
Andet	:	Egenskaber: Hørlig alarm, LCD-skærm, beskyttelse mod overopladning, overbelastningsbeskyttelse, kold-start funktion, automatisk slukning, udladningsbeskyttelse
Batteri	:	2 x 12V/9Ah
Indgangsspænding	:	AC 220/230/240 V
Interface	:	1 x administration (USB) - 4-PIN USB type B
Kabel	:	1 x USB-kabel - ekstern (medfølger)
Mål og vægt	:	320 x 182 x 130 mm, 11 kg med batteri
Spændingsform	:	Modificeret sinus (trappetrin-kurve)
Udgangsspænding	:	230VAC / 50Hz modificeret sinuskurve
Weight	:	11.5 kg

