

350 Watt ATX PS/2 power supply with -5Volt without fan on top

FEATURES

- Input 90~264Vac Auto
- Internal 8 cm fan with IEC 62368 standard vents opening
- Low Ripple Noise
- Support OCP, OTP and OVP circuit protection
- Short circuit protection on all outputs
- Resettable power shut down
- MTBF:100K hours at 25°C
- 100% under high ambient temperature (50°C)80 plus bronze
- 350watt
- ATX
- PS2 format
- industrial
- H 86 x B 150 x D 140





SPECIFICATIONS

Andet	:	Over current protection 3.3V:50mV p-p 5V:50mV p-p 12V1:120mV p-p 12V2:120mV p-p -12V:120mV p-p 5Vsb:50mV p-p -5V:100mV p-p
Approval	:	EN62368
Effekt	:	350 Watt
Forsyning	:	90-264Vac, 47-64Hz, 115Vac@6A, 230Vac@3A
Luftfugtighed	:	Operating : 85% to % RH, Non-condensing Storage : 95% to % RH, Non-condensing
Output	:	+3.3Vdc output : +3.7 Vdc minimum, + 4.8Vdc maximum +5Vdc output : +5.7 Vdc minimum, + 7Vdc maximum +12Vdc output : +13.3 Vdc minimum, + 16Vdc maximum
Støj	:	115V-rms/230V-rms 5V 20ms Maximum 115V-rms/230V-rms 12V 20ms Maximum
Temperatur	:	Operating : 0 to +50°C Storage :-20 to +80°C
Dimensioner	:	140 x 150 x 86mm

