

## Compact Embedded PC Bay Trail 1.91GHz, 2 x POE Ethernet, POC-200, Fanless EOL

### FEATURES

- Ultra compact 150mm x 100mm
- Intel® Atom™ E3845 1.91 GHz Quad-core
- Fanless
- 2 x 802.3at (25.5W) Gigabit PoE ports
- 3 x USB 3.0
- 2.5" SATA HDD/SSD
- Option: built-in eMMC
- Up to two RS-232/422/485 ports and two RS-232 ports
- 25°C to 70°C
- 8~35VDC
- The product is EOL, only those in stock
- Replacement EPC-N4200-DIN+





## SPECIFICATIONS

|                 |   |                                                                                                                                                                           |
|-----------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU             | : | 1.91GHz Intel® Atom™ E3845 Quad-core processor                                                                                                                            |
| USB             | : | 3x USB 3.0 ports and 1x USB 2.0 port                                                                                                                                      |
| Operating Temp. | : | -25°C ~ 70°C with SSD , 100% CPU loading */** -10°C ~ 50°C with HDD, 100% CPU loading */**                                                                                |
| Chok/Vibration  | : | Vibration Operating, 5 Grms, 5-500 Hz, 3 Axes(w/ SSD, according to IEC60068-2-64) Shock Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27) |
| Ethernet        | : | 2x Gigabit Ethernet ports by Intel® PoE IEEE 802.3at (25.5W PSE)                                                                                                          |
| Forsyning       | : | Built-in 8~35V DC Input Connector 1x 2-pin pluggable terminal block for DC input                                                                                          |
| Grafik          | : | Integrated Intel® HD Graphics                                                                                                                                             |
| Harddisk        | : | 1x SATA ports with 2.5" HDD/SSD                                                                                                                                           |
| Hukommelse      | : | 1x SO-DIMM socket for DDR3L-1333, without                                                                                                                                 |
| I/O             | : | 4-CH isolated DI + 4-CH isolated DO                                                                                                                                       |
| Montering       | : | Wall-mounting (standard) or DIN-Rail mounting (optional)                                                                                                                  |
| Porte           | : | 2x RS-232/422/485, 2x RS-232                                                                                                                                              |





Svensk Binär Teknik

EPC-BT-2POE

## SPECIFICATIONS

|             |   |                                                             |
|-------------|---|-------------------------------------------------------------|
| Udgange     | : | 1x DVI-I connector for both analog RGB and DVI/HDMI outputs |
| Udvidelser  | : | 1x mini PCI Express slot with USIM socket                   |
| Weight      | : | 1.1 kg (including one 2.5" HDD)                             |
| Dimensioner | : | 149mm (W) x 105 mm (H) x 57 mm (D)                          |



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.