

8 x Power Relay COM NO, 24VDC / 250VAC 5A, 1 x RJ45 Ethernet Modbus/TCP/UDP, PoE FEATURES

- Built-in web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- Good communication security
- Dual Watchdog
- Operating temperature range: -25 ~ +75°C
- I/O Pair - second module's input is mirrored to output
- 8 x Power Relay - electromechanical, COM NO
- Relay switching time: on: 10ms, off: 5ms
- Relay contact voltage and current: 24VDC/250VAC/5A
- Electromechanical: Avoid inductive load
- Supply voltage: PoE or 12 - 48VDC





Svensk Binär Teknik

ETHIO8PR-P-I

SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 2,5 W via klemrække eller PoE
Netværk	:	10/100 Mbit m/RJ45-stik
Protokol	:	Modbus/TCP, TCP/IP og UDP
Udgange	:	8 stk. relæer (Slutte) maks 250VAC/ 5 A eller 24 volt DC / 5 A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.