

19" i5 ECDIS DNVGL-CG-0339, IACS E10 Marine approved Panel PC, 24VDC

FEATURES

19" 1280 x 1024 Marine approved Panel PC
 Projective multitouch screen PCAP
 Marine standard: DNVGL-CG-0339, IEC60945 4th.
 IACS-E10
 Intel Core i5-5200U 2.2GHz
 4GB RAM, 128GB SSD (mSATA) Dual ethernet
 Supports Win 10 IoT Enterprise (must be purchased separately)
 2 x USB 3.0, 1 x USB2.0
 1 x RS232 (RS422/485)
 2 x RJ45
 Option: 8 ch DI/DO (additional purchase)
 Option: 4 x NMEA 0183 port (additional purchase)
 Supply voltage: 24VDC / 65Watt
 DC input: 9 - 36VDC
 Dimensions: 429 x 382 x 73 mm
 Weight: 7.8 kg





SPECIFICATIONS

CPU	:	Intel Core i5-5200U Broadwell 2.2GHz
Digital I/O	:	8 Channel Isolated Digital Input/Output (Optional)
Operating Temp.	:	-15 to 55 deg.C
Farve	:	16.7 M colors, 8 bits/color
Betragningsvinkel	:	85°/85°/80°/80° (typ.) (Up/Down/Left/Right)
Chok/Vibration	:	Anti-Vibration 0.7g@DNV2.4 (Class A) Anti Shock 15G, 11ms duration
Ethernet	:	Dual Ethernet Gb LAN, 2 x RJ45
Hukommelse	:	1 x DDR3L-1066 SODIMM (Default 4GB,Max 16GB)
Kontrast	:	1000:1 (typ.)
Luftfugtighed	:	5% to 95% (non condensing)
Lyd	:	Buzzer 75 dB~80 dB, 2300 Hz, 1m Speaker 2 x 2W Speaker
Pixels	:	0.294 (H) x 0.294 (V) mm





Svensk Binär Teknik

IPP19IDNV

SPECIFICATIONS

Strømforbrug : 80W

Strømforsyning : 24V DC-in with Isolation (9~36V acceptable), DC Power Signal 1 x 3-Pin Terminal Block (Phoenix type)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.