

IP67 sealed Embedded PC Intel i5-7300U or Celeron 3965U, -30°C ~ +60°C, WIFI, Fanless

FEATURES

- i5-7300U 2.2GHz or Celeron 3965U CPU
- Max. 16 GB of RAM
- 2 x USB (M12)
- 1 x RJ45 Gbit
- 1 x VGA (M12)
- 2 x RS232/422/485 (M12)
- Watchdogtimer
- 1 x 2.5" SATA HDD (max. 9.5mm)
- 1 x mSATA (enabled in BIOS)
- 1 x Full-size and 1 x Half-size PCI Express Mini Card slot (USB + PCIe signal)
- TPM 1.2
- 4 x N-jack antenna opening with water proof design
- Vibration Endurance 3 Grms with SSD (5 to 500Hz, X, Y, Z directions)
- 30°C ~ +60°C
- 210 mm (8.27") x 366.83 mm (14.44") x 83.8 mm (3.27")
- 9~36VDC Power input (M12)
- Support: WIN10IoT & Linux





SPECIFICATIONS

CPU	:	Intel Core i5-7300U onboard
USB	:	2 x USB 2.0 (M12-type)
Operating Temp.	:	-30°C ~ +60°C (-22°F ~ +140°F) (with i5-7300, W.T. SSD/DRAM)
Andet	:	1 x ATX power switch w/indicator 4 x antenna opening N Jack type w/ water proof design
Approval	:	CE, FCC Class A
Chok/Vibration	:	3 Grms with SSD (5-500Hz, X, Y, Z directions)
Ethernet	:	1 x 10/100/1000 Mbps Ethernet (i219-LM, M12)
Grafik	:	1 x VGA (M12-type),
Hukommelse	:	1 x 204-pin DDR4-2133 SO-DIMM up to 16 GB
Luftfugtighed	:	10% ~ 95% , non-condensing
Montering	:	Wall mount, VESA mount 100x100
OS SUPPORT	:	WIN 10 IoT, Linux





Svensk Binär Teknik

EPC-BT-IP67

SPECIFICATIONS

Spænding	:	9~36VDC
Udvidelser	:	1 x full-size and 1 Half-size PCI express Mini Card Slot (USB + PCI express signal),
Weight	:	4.31 Kg (9.5 lb)/5.1 kg(11.24 lb)
Dimensioner	:	210 x 366.83 x 83mm (8.27" x 14.44" x 3.27")



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.