

RS232 / 422/485 to HART Convert, Hart Terminal
Block for 2-wire. 10 - 30vdc.

FEATURES

FEATURES

- Serial to HART Convert
- Allows 2 pcs. Hart Masters
- Point-to-Point or Multi-Drop Hart Mode
- Possibility of connecting 15 HART modules
- Point-to-point or multi-drop HART mode for configuration of modules
- Isolated COM 1: RS-232 / 422/485
- PWR / RUN / ERR INDICATION LED
- Built-in Watchdog
- 4 kV ESD protection





SPECIFICATIONS

Operating Temp.	:	-25 °C ~ +75 °C
Baudrate	:	1200 bps (For FW_v1.1)
Data	:	O(odd parity), 8(data bit), 1(stop bit) (For FW_v1.1)
Interface	:	COM 1: RS-232(Tx / Rx / GND) / RS-422 / RS-485.COM 1 Connector: 9-pin screwed terminal block. HART Interface: 2-pin screwed terminal block. HART Channel: 1
LED	:	PWR / TxD / RxD
Montering	:	DIN-Rail or Wall Mounting
Strømforsyning	:	Unregulated +10 ~ +30 VDC
Dimensioner	:	121 mm x 72 mm x 35 mm (H x W x D)

