

M485-ETH-CAN

Ethernet to Can Device Server. CAN to Ethernet
Gateway. With 1 x CAN, RS232 and RS485.

FEATURES

- Internet Communication controller with 1 x CAN bus, 1 x RS-232, 1 x RS-485 and 1 x Ethernet 10/100 Base-TX Ethernet controller
- TCP / IP protocol
- 80 MHz CPU
- 1 x RS-232 port, 1 x RS-485 port and 1X CAN port can be used simultaneously
- Max Transmission Speed up to 1M BPS for CAN and 115.2Kbps for RS-232 RS-485
- 7 -Segment LED Display
- Software Configuration for Can and RS-232
- Web Configuration
- Up to 25 Ethernet Client Connections
- Supports Virtual Com



SPECIFICATIONS

Operating Temp.	:	-25 ~ 75 °C
Controller	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Power supply Unregulated +10 ~ +30 VDC Protection Power reverse polarity protection, Over-voltage brown-out protection Power Consumption 2.5 W
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Stik	:	CAN BUS: 2-pin screwed terminal block. COM 1 Connector 5-pin screwed terminal block (Tx, Rx, RTS, CTS, GND). COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
Dimensioner	:	(W x L x H) 72mm x 122mm x 33mm

