

M485-REL4D-I

4 x relay outputs, (2 NO, NC and 2 NO) 4 x digital inputs, and isolated with the display, RS485 bus, 10 - 30VDC

FEATURES

- RS485 relay box with the display
- 4 x relay outputs 2 and connect switch 2
- 4 x isolated inputs
- Supply 10 to 30
- RS485 Communication port
- 16 bit counter
- ON Voltage Level: 4 V 30 ~ V
- OFF Voltage Level: 0 ~ 1 V V
- Insulation Voltage: 3750 Vrms
- Input Resistance: 3 kΩ, 0.25 W
- Dual Watchdog





SPECIFICATIONS

Operating Temp.	:	-25 ~ +75°C
Andet	:	Contact Rating 0.6 A @ 125 VAC 2 A @ 30 VDC
Baudrate	:	1200 ~ 115200 bps
Forsyning	:	10 ~ 30 VDC 1.4 W via klemrække
Indgang	:	4 optoisolerede digitale indgange, Isolationsspænding: 3750
Indgangsimpedans	:	3 kΩ
Interface	:	RS-485 Modbus RTU, DCON
LED	:	Yes, 1 LED as Power/Communication Indicator I/O LED Indicators --- Yes, 8 LEDs as Digital Input/Relay Output Indicators
Montering	:	DIN-Rail or Wall Mounting
Protokol	:	DCON
Udgange	:	4 relæer 2 type A (slutte), 2 type C (skifte)
Watchdog	:	Yes, Module (1.6 Seconds), Communication (Programmable)

