

M485-DIO7D-I

7 digital inputs and 8 digital outputs, display. RS485 bus. 10 - 30vdc.

FEATURES

- RS485 module with digital I / O
- 7 digital input
- 8 digital output, 30volt / 30mA
- RS485 interface
- Baudrate 1200 ~ 115200 bps
- Dual Watchdog
- 10 - 30 VDC, 1 W via terminal block
- 25- + 75 °
- DIN rail mounting



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	:	25 ~ +75°C
Baudrate	:	1200 ~ 115200 bps
Indgang	:	7 stk. med fælles minus. Indbyggede Pull-up": 10 kΩ til 5 VDC Logisk 0: 0 - 1 V Logisk 1: 4 - 30 V
Interface	:	RS-485
LED	:	Yes, 1 LED as Power/Communication Indicator
Montering	:	DIN-Rail or Wall Mounting
Protokol	:	DCON (For I-7050 series) Modbus RTU, DCON (For M-7050 series)
Udgange	:	8 stk. "Open collector": 30 V/30 mA, maks. effekt: 300 mW
Watchdog	:	Dual Watchdog. Module (1.6 Seconds), Communication (Programmable)

