

## 19 "DNV Marine Approved Panel Monitor, Supply 24Vdc, 5: 4 Format

### FEATURES

19 "DNV2.4, IEC60945 Marine Monitor Without  
Touch  
400 Nits  
IP66  
Resolution: 1280x1024 - 5: 4 Format  
Active Display Area: 376.32 (H) x 301.06 (V) mm  
1 x composite (RCA phono)  
1 x DVI-D  
1 x S-Video (SVHS)  
1 x RBG (D-SUB)  
Power Supply: Terminal block 24V DC  
Mounting: Panel (Flush) mount with IP66 \*, VESA,  
Bracket mounting  
Anti vibration: 5Hz - 500Hz / 1Grms / 3Axis  
Anti shock: 15G, 11ms duration  
Optional: AC power signal Std IEC Inlet  
Optional: Touch Screen D-SUB 9P Female  
Optional: Remote Control via RS232 D-SUB 9P





## SPECIFICATIONS

|                          |   |                                                                                                                                                                                                                                    |
|--------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp.          | : | -15 ~ +55°C                                                                                                                                                                                                                        |
| Approval                 | : | DNV2.4,IEC60945,IACS-E10,CE,FCC                                                                                                                                                                                                    |
| Betjening                | : | Power On/Off via Front Button, VR Brightness Knob Control                                                                                                                                                                          |
| Chok/Vibration           | : | Anti-Vibration 5Hz~500Hz / 1Grms/3 Axis Anti Shock 15G, 11ms duration                                                                                                                                                              |
| Grafik                   | : | 19", Res 1280 x 1024, Pixel Pitch (RGB) 0.294 (H) x 0.294 (V) Contrast Ratio 1000:1 (typ.) Brightness 400 (typ.) Viewing Angle -85~85 (H); -80~80 (V) Active Display Area 376.32 (H) x 301.06 (V) Max Colors 16.7M (8bits/ colors) |
| Indikatorer og kontakter | : | LED indicators Power Mode Status LED                                                                                                                                                                                               |
| IP-Tæthed                | : | Front IP66, (saw touch IP54)                                                                                                                                                                                                       |
| Luftfugtighed            | : | 5% to 95% (non-condensing)                                                                                                                                                                                                         |
| Montering                | : | Vesa, and stand (stand bracket is option)                                                                                                                                                                                          |
| OSD                      | : | On Screen Display control (OSD)                                                                                                                                                                                                    |
| Skærm                    | : | 19" Transflective                                                                                                                                                                                                                  |
| Strømforsyning           | : | 24Vdc DC Power Signal Screw terminal block                                                                                                                                                                                         |





Svensk Binär Teknik

MON-MAR19"

## SPECIFICATIONS

Weight : 5.4 Kg



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.