

19" ECDIS panel tft maritime approved (DNVGL-CG-0339, IACS E10, IEC 60945 4th edition), 24VDC, PCAP multitouch, 5:4 format

FEATURES

Maritime approved 19" panel monitor (DNVGL-CG-0339, IACS E10, IEC 60945 4th edition)
 Brightness: 400 cd/m² (nits)
 Protection class (front): IP66
 Resolution: 1280 × 1024 (5:4)
 Active viewing area: 376.32 (W) × 301.06 (H) mm
 Video inputs: 1 × VGA, 1 × HDMI 1.4, 1 × DVI-D
 Power supply: 24 V DC via terminal block
 DC input: 9-36 V DC / typical 45 W
 Mounting: recessed panel mounting (flush) with IP66 front*, VESA 100 or bracket mounting
 Vibration: 0.7 g according to DNVGL CG-0339 (class A)
 Shock: 15g, 11ms
 Option: remote control via RS-232 (D-Sub 9-pin)
 Dimming (DIM): day / dusk / night
 Dimensions: 429 × 382 × 73 mm • Weight: 9.8 kg





Svensk Binär Teknik

MON-MAR19"T

SPECIFICATIONS

Operating Temp.	:	-15 to 55 deg.C
Montering	:	Panel (Flush) mount with IP66*, VESA, Bracket mounting
Strømforsyning	:	24V DC terminal block
Touch	:	PCAP, USB
Dimensioner	:	483 x 479 x 75mm (L x H x B)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.