

ETH2SER5230A

2 Ports serial port server RS422 / 485 Optoisolated, Moxa Nport 5230A-T. Serial Device Server FEATURES

- External COM ports via Ethernet and Internet
- Serial Device Server with RS422 or RS485 via Ethernet and Internet.
- RS422 / 485 seriesport via screw terminal
- Dual DC Power input with Power Jack and Terminal block
- Power supplies from 12 - 48VDC
- DIN mounting





ETH2SER5230A

SPECIFICATIONS

Operating Temp.	:	0 to 60°C
Andet	:	Ethernet Line Protection EN 61000-4-5 (Surge) Level 2
Forsyning	:	Power Requirements Input Voltage 12 to 48 VDC Input Current 119 mA @ 12 VDC
Hastighed	:	10/100 Mbps, auto MDI/MDIX
Isolation	:	1.5 kV built-in
Materiale	:	Metal
Porte	:	2
Protokol	:	Network Protocols ICMP, IPv4, TCP, UDP, DHCP, BOOTP, Telnet, DNS, SNMP V1, HTTP, SMTP, IGMP V1/2, ARP
Signaler	:	RS-422 Tx+, Tx-, Rx+, Rx-, GND RS-485-4w Tx+, Tx-, Rx+, Rx-, GND RS-485-2w Data+, Data-, GND
Stik	:	8-pin RJ45
Watchdog	:	Built-in WDT (watchdog timer)
Weight	:	340 g





Svensk Binär Teknik

ETH2SER5230A

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.