

ANR-LNX-1002G-10G

8 ports Industrial 10/100 / 1000Mbit switch + 2 x
10Gbit SFP slot, unmanaged, DIN bracket, -40 - + 60
° C, 12 - 48VDC

FEATURES

- 8 port 10/100 / 1000Mbps switch and 2 port 10Gbps SFP + fiber slots
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 16K MAC Address Table
- 9,216 bytes Jumbo Frame Support
- Surge Protection: 2,000 VDC Support
- ESD Protection: 6,000 VDC Support
- Redundant Power Input Design: 12 ~ 48VDC
- 1 Relay Output for Power Failure Warning
- IP30 Rugged Metal Case Design
- DIN-Rail and Wall Mount Support
- Temperature range: -40 ° to 60 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



ANR-LNX-1002G-10G

SPECIFICATIONS

Operating Temp.	:	-40 - +60
Fiber	:	2 x 10Gbit SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	16 Watt
Netværk	:	8 x RJ45, 10/100/1000Mbit
Dimensioner	:	54 x 99 x 142mm

