

ANR-LNX-1202G-10G

10 ports Industriel 10/100/1000Mbit switch + 2 x
10Gbit SFP slot, unmanaged, Din-beslag, -40 - +60°C,
12 - 48VDC

FEATURES

- 10 port 10/100/1000Mbps switch og 2 port 10Gbps SFP+ fiber slots
- Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- 16K MAC Address Table
- 9,216 bytes Jumbo Frame Support
- Surge Protection: 2,000 VDC Support
- ESD Protection: 6,000 VDC Support
- Redundant Power Input Design: 12~48VDC
- 1 relæ output til Power Failure Warning
- IP30 Rugged Metal Case Design
- DIN-Rail and Wall Mount Support
- Temperaturområde: -40° to 60° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



ANR-LNX-1202G-10G

SPECIFICATIONS

Operating Temp.	:	-40 - +60
Fiber	:	2 x 10Gbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	16 Watt
Netværk	:	10 x RJ45, 10/100/1000Mbit
Dimensioner	:	54 x 99 x 143

