

5 ports Industriel 10/100/1000Mbit + 2 x
100/1000Mbit SFP slot switch, DIN-beslag, -40 -
+75°C, 12 - 48VDC

FEATURES

- 5 x 10/100 / 1000Mbps Ethernet ports + 2 x 100 / 1000Mbps SFP Slot
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 10Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame Support
- Surge Protection: 3kV
- ESD Protection: 6kV
- Redundant Power Input Design - 12 ~ 48VDC
- 1 Relay Output to Port Break Alarm
- IP30 Aluminum Cabinet
- DIN-Rail and Wall Mount
- Temperature Range: -40 to 75 ° C





Svensk Binär Teknik

ANR-LNX-0702G-SFP-T

SPECIFICATIONS

Operating Temp.	:	-40 - +75
Fiber	:	2 x 100/1000Mbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	9,1 Watt
Netværk	:	5 x RJ45 10/100/1000Mbps



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.