

ANR-LNX-1002G-SFP

8 ports Industriel 10/100/1000Mbit + 2 x
100/1000Mbit SFP slot switch, DIN-beslag, -10 -
+70°C, 12 - 48VDC

FEATURES

- 8 ports 10/100 / 1000Mbps Fast Ethernet switch +
- 2 100 / 1000Mbps SFP slot
- Auto MDI / MDI-X Function
- Store and Forward Switching Architecture
- 20Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame Support
- Surge Protection: 3,000 VDC
- ESD Protection: 6,000 VDC
- Redundant Power Input - 12 ~ 48VDC
- 1 Relay Output to Port Break Alarm
- IP30 Aluminum housing
- DIN-Rail and Wall Mount
- Temperature range: -10 ° to & nbsp; 70 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



ANR-LNX-1002G-SFP

SPECIFICATIONS

Operating Temp.	:	-10 - +70
Fiber	:	2 x 100/1000Mbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	10 Watt
Netværk	:	8 x RJ45, 10/100/1000Mbit
Dimensioner	:	46 x 99 x 142mm

