

5 ports Industrial 10/100 / 1000Mbit switch, DIN rail,
-40 - + 75 ° C, 12 - 48VDC

FEATURES

- 5 x 10/100 / 1000Mbps Ethernet Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 10Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame Support
- Surge Protection: 2kV
- ESD Protection: 6kV
- Redundant Power Input Design - 12 ~ 48VDC
- IP30 Aluminum Cabinet
- DIN-Rail and Wall Mount
- Temperature range: -40 ° to 75 ° C





Svensk Binär Teknik

ANR-LNX-C500G-T

SPECIFICATIONS

Forsyning	:	12 - 48VDC, redundant
Kabinet	:	Metal, IP30, DIN-beslag,
Maks. effekt	:	6,6 Watt
Netværk	:	5 x RJ45, 10/100/1000Mbps
Dimensioner	:	26 x 95 x 75mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.