

ANR-LNP-2804GN-SFP-T

24 ports Industrial 10/100 / 1000Mbit + 4 x 100 / 1000Mbit SFP, combi, managed PoE switch. Rack. -40 - + 75 ° C, 46 - 57VDC

FEATURES

24 x 10/100 / 1000Tx IEEE 802.3 Off / On, PoE + Gigabit Ports (30W / Port) + 4 x Gigabit Copper / SFP Combi Ports
4 x 10/100 / 1000Tx RJ45 + 4 x 100/1000 SFP Slots
Management: SNMP v1 / v2c / v3, WEB, Telnet, Standard MIB
Security: 802.1x (Port Based, MD5 / TLS / TTLS / PEAP Encryption), HTTPS, SSH and SNMPv3
Redundant : Proprietary Ring (Ultra-High-Speed Recovery Time <20 ms), RSTP / STP (802.1w / 1D), MSTP
48VDC Power Input (46-57 VDC for PoE off, 53-57 VDC recommended for PoE at) 2 Relay Outputs
Temperature: -40 ° - 75 ° C - Polarity Protection
Overload Protector
1U Rack Mount Design
IP30 Close



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Operating Temp.	:	-40 - +75
Fiber	:	4 x 100/1000Mbps SFP slot
Forsyning	:	46 - 57VDC, redundant
Kabinet	:	1U, 19" rack, metal, IP30
Maks. effekt	:	20 Watt system, 30 Watt per PoE port, maks. 480 Watt
Netværk	:	24 x 10/100/1000Mbps, RJ45, PoE+
Protokol	:	IGMP, SNMP, TFTP, SNMP, SMTP, Syslog, Web-browser, Ring, IPv6
Dimensioner	:	438 x 43,6 x 259,2mm, 1U, rack

