

ANR-LNX-1802GN

16 ports Industriel 10/100 + 2 ports 100/1000Mbit SFP slot (combi), managed switch. DIN-beslag. -10 - +70°C, 12 - 48VDC

## FEATURES

- 16 x 10/100Mbps RJ45
- 2 x 10/100/1000Mbit RJ45 (combi)
- 2 x 100/1000Mbps SFP slot (combi)
- 7.2 Gbps Back-Plane (Switching Fabric)
- Ethernet Ring Redundancy (Recovery Time <20ms)
- IEEE 802.1w Rapid Spanning Tree & IEEE 802.1d Spanning Tree Protocol
- IEEE 802.1x RADIUS
- IEEE 802.1p Class of Service for Traffic Classification & Prioritization
- QoS (Quality of Service)
- Port Based VLAN & IEEE 802.1Q Tag VLAN
- IGMP med Query Mode for Multi-Media applikationer
- Port Mirroring for Traffic Monitoring
- IP Address Security Management
- IP30 robust aluminum kabinet
- DIN-Rail eller vægmontering



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



## SPECIFICATIONS

|                 |   |                                    |
|-----------------|---|------------------------------------|
| Operating Temp. | : | -10 - +70                          |
| Fiber           | : | 2 x 100/1000Mbps SFP slot          |
| Forsyning       | : | 12 - 48VDC, redundant              |
| Kabinet         | : | Metal, IP30, DIN-beslag, vægbeslag |
| Maks. effekt    | : | 11,5 Watt                          |
| Netværk         | : | 16 x 10/100Mbps RJ45               |
| Dimensioner     | : | 72 x 152 x 105mm                   |

