

ANR-LMP-1204G-SFP-T

8 ports Industrial 10/100 / 1000Mbit PoE + 4 x 100 / 1000Mbit SFP switch, DIN rail, -40 - + 75 ° C, 48 - 55VDC

FEATURES

- 8 x 10/100/1000Mbps RJ45 med PoE+ (30W)
- 4 x 100/1000Mbps SFP slot
- Netværk redundancy: STP/RSTP/MSTP, og G.8032 ERPS (Recovery Time <50ms)
- IPv4/IPv6, og DHCP option 66/67/82
- Modbus/TCP protocol for Device Management og monitoring
- Konfiguration: Web Console, Telnet, CLI Command
- PoE, ping alarm funktion for PoE porte
- IGMP v1/v2 for Multicast Traffic Filtering
- Udvidet netværk security med IEEE802.1X, SNMP v1/v2c/v3, HTTPS, og SSH/SSL
- Port lock function for unauthoriserede address blokering
- Automatisk advarsel via e-mail og via relæudgang
- Temperatur: -40 - +75°C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Operating Temp.	:	-40 - +75
Fiber	:	4 x 100/1000Mbps SFP slot
Forsyning	:	48 - 55VDC, redundant
Kabinet	:	Metal, IP30, DIN-beslag, vægbeslag
Maks. effekt	:	15 Watt system, 255 Watt ved PoE+ på alle porte
Netværk	:	8 x 10/100/1000Mbps RJ45, PoE+ (30 Watt per port)
Protokol	:	IGMP, SNMP, TFTP, SNTP, SMTP, Syslog, Modbus/TCP. IPv4/6
Dimensioner	:	54 x 142 x 99mm

