

10.4 Panel PC medico godkendt EN 60601-1 FEATURES

10.4 "XGA TFT LCD display with LED backlight
Intel® Celeron® processor N3060
2 Gigabit LAN to 4 USB
two COM ports, you can choose RS-232/422/485 in the BIOS
Plastic
Front IP65 close
available with support for RFID (optional)
Vesa mount, wall mount desk stand
Meets 4th EN 60601-1 (ESD contact 8KV, air 15kV)
CE, FCC certified





SPECIFICATIONS

CPU	:	Intel® Celeron® processor N3060 up to 2.48 GHz
Chipset	:	SoC Integrated
Operating Temp.	:	0°C ~ +40°C (+32°F ~ +122°F)
BIOS	:	AMI
Approval	:	EN 60601-1, CE and FCC
Ethernet	:	2 x 10/100/1000 Mbps (Intel® i211AT)
Forsyning	:	AC version: 100 ~ 240 V AC-DC, 60W power adapter or DC version: 9 ~ 36 VDC with overcurrent protection fuse
IP-Tæthed	:	IP65, NEMA 4 rugged protection, plastic front bezel
LCD	:	10.4" XGA TFT 350 nits 1024 x 768 pixels
Lyd	:	Line-out
Montering	:	VESA arm Panel mount Desktop stand
OS SUPPORT	:	Windows® 10, Windows® 8.1, WE8S, Windows® 7, WES7





Svensk Binär Teknik

IPP10.4MEDIC

SPECIFICATIONS

Touch	:	Resistive Type
Udvidelser	:	1 x full-size PCI Express Mini Card slot with mSATA slot 1 x full-size PCI Express Mini Card slot with SIM slot
Watchdog	:	255 levels, 0 ~ 255 sec.
Weight	:	1.8KG
Dimensioner	:	292.5 x 45.8 x 235.8 mm (11.52" x 1.80" x 9.28") (W x D x H)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.