

HDMI-MULTI-HD-R

HDMI Extender 1080p HD over IP network, with PoE,
or point to point with PDS cable. Receiver module.
Purchase Transmitter

FEATURES

- HDMI Video Receiver with PoE
- Transmitter Module is purchased: HDMI-Multi-HD-T
- Video Wall with a maximum of 64 units
- H.264 Video Encoder / Decoder, IR transfer
- Delay of approximately 1 second from transmitter to receiver
- HDMI 1.4a
- Connection over IP - Use switch with IGMP Snooping
- Max. 64 Groups
- Range Up to 100m - Point to Switch or to Transmitter
- Cables Cat 6a. Good quality
- Edid Emulation - possibly not on all screens, then buy it from Danbit
- 1 x RJ45, 1 x DB-9, 1 x HDMI exits
- Supply IEEE 802.3AF / to POE + or 5V DC, 2a (not included)
- Requires quality switch When used over IP
- Dim: 130 x 82 x 30 mm





SPECIFICATIONS

Operating Temp.	:	0-50°
Andet	:	EDID (Extended Display Identification Data) function
Båndbredde	:	15Mbps (max.)
Forsyning	:	IEEE 802.3af/at PoE+; 5V DC, 2A
Kabel	:	Cat5e/6 UTP cable
Kanaler	:	DIP (64 channels)
Opløsning	:	Video In Resolution: 1080p @ 60/50 Hz 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz Video Out Resolution: 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz
Porte	:	1 x RJ45, 1 x DB-9, 1 x HDMI out
Protokol	:	TCP, UDP, RTSP, RTP, DHCP, IGMP Snooping, Multicast, IPv4
Rækkevidde	:	100 meters (330 feet) over CAT5e/6 cable
Sikkerhed	:	HDCP compliant
Standarder	:	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3af/at PoE+





Svensk Binär Teknik

HDMI-MULTI-HD-R

SPECIFICATIONS

Dimensioner : 130 x 82 x 30.25 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.