

HD HDMI extender over IP med PoE - Digital Signage, sendermodul

FEATURES

- HDMI video transmitter PoE
- Suitable for video wall
- With HDMI Loop Out
- Delay of approx. 1 second from transmitter to receiver
- HDMI 1.4a - H.264
- By IP multicast use switch with IGMP Snooping
- Range up to 100m
- Cables Kat. 5th / 6
- EDID Emulation
- IR Transfer
- 1 x RJ45, 1 x DB-9, 1 x HDMI Input, 1 x HDMI Output
- Supply IEEE 802.3af / at PoE +; 5V DC, 2A (not supplied)
- As receiver, use HDMI-MULTI-HD-M





SPECIFICATIONS

Operating Temp.	:	0-50°
Andet	:	EDID (Extended Display Identification Data) function
Båndbredde	:	15Mbps (max.)
Forsyning	:	IEEE 802.3af/at PoE+ 5V DC, 2A
Kabel	:	Cat5e/6 UTP cable
Kanaler	:	DIP (64 channels)
Lyd	:	2-ch uncompressed audio
Opløsning	:	Video In Resolution: 1080p @ 60/50 Hz 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz Video Out Resolution: 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz
Porte	:	RJ45, 1 DB-9, 1 HDMI In, 1 HDMI Out
Protokol	:	TCP, UDP, RTSP, RTP, DHCP, IGMP Snooping, Multicast, IPv4
Rækkevidde	:	100 meters (330 feet) over CAT5e/6 cable
Sikkerhed	:	HDCP compliant





Svensk Binär Teknik

HDMI-MULTI-HD-T

SPECIFICATIONS

Weight : 290 g

Dimensioner : 130 x 82 x 30.25 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.