

USB to RS232 / RS422 / RS485 high-speed adapter up to 921.6 kbps, 3kV DC isolation

FEATURES

- High-speed USB to RS232/422/485 adapter
- Transmission speed - up to 921.6 kbps
- Supports USB 1.2/2.0/3.0
- 3000V DC isolation on RS232/422/485
- RS232/422/485 cannot be used simultaneously
- Supplied via the USB port
- Automatic RS485 Direction Control
- Temperature range: -25°C - +75°C
- DIN rail mounting
- Windows 98/ME/2000/XP/Vista (32/64-bit)
- Windows 7 / 8.1 / 10 (32/64-bit)
- Win 2012
- Linux





SPECIFICATIONS

Operating Temp.	:	-25 °C ~ +75 °C
Afstand	:	RS-422/485 Transmission afstand : Max. 1,200 m at 9.6 kbps; Max. 400 m at 115.2 kbps
Forsyning	:	+5 VDC via USB
Installation	:	DIN-Rail montering
Interface	:	USB 1.1/2.0/3.0
Isolation	:	3000V DC
Kabinet	:	Brandhæmmende materialer (UL94-V0 level)
Luftfugtighed	:	10 ~ 90% RH
Software	:	
Stik	:	USB type B og RS232/422/485
Strømforbrug	:	0.5 W
Dimensioner	:	(W x H x D) 72 mm x 115 mm x 35 mm

