

## 4 x isolated digital input (counter) and 4 x relay output - DCON and Modbus RTU -25 ~ +75°C FEATURES

- 4 x Digital input and 4 x relay output
- Form A and Form C Power relay
- Source and Sink type of D/I
- D/I the entries is also 16-bit counter
- Configurable Power-on settings
- Configurable Safe Value setting
- Dual Watchdog
- Temperature range -25 to + 75 ° C
- Supply voltage: 10 - 30VDC
- DIN bracket





## SPECIFICATIONS

|                  |   |                                                                                                              |
|------------------|---|--------------------------------------------------------------------------------------------------------------|
| Operating Temp.  | : | -25 - +75 °C                                                                                                 |
| Baudrate         | : | 1200 ~ 115200 bps                                                                                            |
| Forsyning        | : | 10 ~ 30 VDC, 1.4 W                                                                                           |
| Indgang          | : | 4 x Digital input                                                                                            |
| Indgangsimpedans | : | 10 kΩ                                                                                                        |
| Interface        | : | RS-485 Modbus RTU, DCON                                                                                      |
| Isolation        | : | Intra-Module Isolation, Field-to-Logic 3750 VDC                                                              |
| LED              | : | 1 xLED as Power/Communication Indicator. I/O LED Indicators: 8 LEDs as Digital Input/Relay Output Indicators |
| Montering        | : | Wall, DIN-Rail mount                                                                                         |
| Protokol         | : | Modbus RTU: Slave, DCON: Slave                                                                               |
| Stik             | : | Screw Terminal                                                                                               |
| Tæller           | : | Max Count 65535 (16-bit) Max. Input Frequency 100 Mhz Min. Pulse Width 5 ms                                  |





Svensk Binär Teknik

M485-REL4P-I

## SPECIFICATIONS

Watchdog : Yes

Dimensioner : 72 mm (W) x 123 mm (H) x 35 mm (D)



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.