



Svensk Binär Teknik

CNV-CAN-FIBER-SM

CAN bus to Single Mode Fiber. CAN 2.0A, CAN 2.0B. Manual CAN baud rate sw - 10K -1Mbps. 10 - 30VDC FEATURES

Baud rate (bps): 10K - 1M
Terminator Resistor: 120 Ohms
3000VDC DC-to-DC isolation 2500Vrms for photo-couple
ISO 11898-2, CAN 2.0A and CAN 2.0 B
SC single mode, 1310 nm
RS-232 COM1
+10 - + 30VDC unregulated
-25 - + 75 degree driftemperatur
10-90% humidity



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	:	-25 - +75°C
Baudrate	:	10k - 1M (bps)
Fiber	:	SC single mode, 1310 nm
Forsyning	:	+10 ~ +30VDC ureguleret
Isolation	:	3000VDC DC-til-DC isolation, 2500Vrms til photo-couple
Luftfugtighed	:	10% ~ 90%
Protokol	:	CAN bus
Stik	:	DB 9, SC single mode
Terminering	:	120 ohm termineringsmodstand

