

8 "LCD monitor, touch, with LED back light, IP55 close front, 800nits, readable in sunlight, -20°C to +60°C, 4:3 format

FEATURES

8" TFT LCD Monitor, Suitable for Vehicles
Resistive Touch (USB)
LED Backlight
800 x 600 Pixels (SVGA)
Brightness: 800 cd/m² (800nits)
Readable in sunlight
Contrast 500:1
1 x SD / MMC / MS card reader, 1 x USB A, 1 x Microphone
In DVI connector (VGA, 1 x USB and 1 x 12VDC)
Supply 9-36VDC, 15W
Operating Temperature -20 to 60°C
IP55 Front
For VESA 75, Panel Power. wall mount
Dimensions: 207mm x 173mm x 36.7mm (W x H x D)





SPECIFICATIONS

Operating Temp.	:	-20°C to 60°
Andet	:	2 x Built-in speakers (1.2W)
Chok/Vibration	:	Vibration (random): 2.5g@5 ~ 500 Hz □ Vibration Operating: MIL-STD-810G, 514.6 Procedure 1, Category 4, Ground Vehicle – Highway Truck Storage: MIL-STD-810G, 514.6 Procedure 1, Category 4, Integrity Test □ Shock
Interface	:	Lateral: 1 x SD/MMC/MS card reader, 1 x USB type A Host, 1 x Line-out 1 x Mic-in Interface Bottom: 1 x Mic-out, 1 x Line-in, 1 x DVI-D Connector (integrating VGA, USB x 1 and 12VDC x 1)
IP-Tæthed	:	Front panel IP55
Kontrast	:	Contrast ratio: 500 : 1 (typical)
Lysfølsomhed	:	Sunlight-Readable Display with High Brightness LCD (800 cd/m2)
Materiale	:	Enclosure: Plastic PC + ABS
Montering	:	VESA 75, panel and wall mounting
Pixels	:	
Skærm	:	8" SVGA TFT LCD Monitor
Touch	:	4-wire resistant touch Anti-glare coating surface Transmission rate: 82 ± 3%





Svensk Binär Teknik

MON8-TFT-S

SPECIFICATIONS

Dimensioner : 207mm (W) x 173mm (H) x 36.7mm (D)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.